

Surefire Fury P3X



Specifications

Output / Runtime -- White Light

High 100 .0 lumens / 2.25 hours
0

Low 15 lumens / 60 hours

Tactical 2 .2

Runtime* 5

Length 6 .8 inches

Bezel Diameter 1 .3 inches

7

Weight 7 .2 ounces

w/Batteries

Batteries 3 123A (included)

*Runtime until output drops below 10% of maximum output at this setting

Description

P3X-B-BK

The P3X Fury has a virtually failure-proof ultra-high-output LED that delivers your choice of either 1,000 blinding lumens of perfectly focused light or 15 lumens of useful light. The 1,000-lumen output — with peak beam level of 22,000 candela — is enough for searching, signaling, or to overpower the dark-adapted vision of

a threat. The 15-lumen output level is perfect for general work at close-to-medium distances and lets you greatly extend the flashlight's runtime on a set of three lithium 123A batteries, a valuable feature when in the field or in remote locations without easy access to spare batteries. At either setting, a precision reflector delivers a smooth, far-reaching beam with a brighter central area and generous peripheral light to help maintain situational awareness.

The P3X Fury is activated with a click-type tailcap switch: press for momentary-on low, press further to click constant-on low, return to off and press or click on again within two seconds for high. The high-strength aerospace aluminum body is smoothly sculpted for a comfortable, secure grip in all kinds of weather and is coated with a Mil-Spec hard-anodized finish for extreme resistance to scratches, abrasion, and corrosion in even the harshest environments.

Features

- Virtually indestructible, ultra-high-output LED emitter regulated to maximize output and runtime
 - Two output levels — high for maximum light, low for extended runtime
 - Precision reflector creates smooth, optimized beam with plenty of reach and enough surround light for peripheral vision
 - Coated tempered window resists impact, maximizes light transmission
 - High-strength aerospace aluminum body, Mil-Spec hard anodized for extreme durability
 - Dual-output tailcap switch—press for momentary-on low, click for constant-on low, return to off and then press or click again for high
 - Tailcap switch locks out to prevent activation during transport or storage
 - Weatherproof O-ring and gasket sealing
- Includes high-energy 123A batteries with 10-year shelf life